

XS-GS80L

8" GS series SVC subwoofer

The XS-GS80L SVC subwoofer cone is constructed using a Mica Reinforced Cellular honeycomb design for reduced weight and increase rigidity, delivering deep bass response.



Bullets

- 8" Single Voice Coil subwoofer
- Mica Reinforced Cellular Glass Fiber Honeycomb cone design
- Single 4 Ohm voicecoil
- Gold plated 5-way binding posts
- 900W Peak (220W Rated)
- 280 Watts CEA 2031 RMS Power
- 3 year warranty

Features

Subwoofer design

The XS-GS80L SVC subwoofer cone is constructed using a Mica Mica Reinforced Cellular Honeycomb design for reduced weight and increase rigidity, delivering deep bass response. The 5-way gold plated binding post provide secure wire connections for high power handling.

High energy magnets

The XS-GS80L woofer uses a powerful, high energy Ferrite magnet to control cone travel and deliver big power handling.

Power handling

The XS-GS80L subwoofer is rated for 280 Watts, 220 Watts RMS (CEA 2031 rated) and can handle peak power of 900 Watts.

Warranty

The Sony® GS series subwoofers come with a 3 year warranty.

Specifications

Audio		Dimensions (Approx.)	8" (20cm)
Frequency Response	28 - 500Hz	Dimensions (Approx) Depth	3 7/8"
Impedance	4 Ohms	Mounting Dimensions (Approx.)	7 1/8"
Sensitivity (db)	84 +/-2dB (1W, 1m)	Weight (Approx.)	5 lb. 2 oz.
General		Supplied Accessories	
Magnet	Ferrite	Supplied Accessories	Parts for installation
Material	Mica Reinforced Cellular Honeycomb cone design		
Power			
Power CEA 2013 RMS	220 Watts CEA2031 RMS		
Power Maximum Capacity	900 Watts		
Rated Power	280 Watts		
Weights and Measurements			
Depth (Approx.)	3 7/8"		
Diameter (Approx.)	8"		



© 2013 Sony Electronics Inc. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Sony is a trademark of Sony. All other trademarks are the property of their respective owners. Features and specifications are subject to change without notice. Updated: January 9, 2013